

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CD44BS
Minimum Qty (MOQ):	170 EA
NSN:	5320-00-494-6436
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N CD44BS Specifications

Fastener Length:	0.357 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.035 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	215 Single Pounds Per Square Inch
Special Features:	Break Stem
Material:	Copper Body
Material:	Steel Mandrel
Surface Treatment:	Copper Overall
Test Data Document:	07707-mil-r-24243 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CD44BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.