

Description

Thread Size: 3/16", Nut Length: 61/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | CH10B216 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-00-947-7018 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CH10B216 Specifications

| | |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.391 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Err Default: | +0.166/+0.216 Inches |
| Shank End Type: | Closed |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Head Countersink Angle: | 100.00 Degrees Nominal |
| Material: | Steel Comp 4037 Overall |
| Material Document And Classification: | Qq-w-405 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/CH10B216> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.