

P/N CHT4067-3-8A

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: CHT406738A

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-369-4811

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N CHT4067-3-8A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Nominal
Fastener Length:	0.890 Inches Minimum And 0.937 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.349 Inches Minimum And 0.381 Inches Maximum
Head Height:	0.0439 Inches Minimum And 0.0459 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Features Provided:	O Ring And Cetyl Alcohol Lubricant
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip32.0 Microinches Threads
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/CHT4067-3-8A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.