## P/N CLS-632-3

### **Description**

Thread Size: 1/8", Nut Height: 1/8",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: CLS6323

Minimum Qty (MOQ): 50

NSN: 5310-00-803-4994


Schedule B: 7318.16.0060

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc







# **P/N CLS-632-3 Specifications**

Thread Class:	2b
Thread Direction:	Right-hand
Pilot Diameter:	0.185 Inches Nominal
Pilot Length:	0.087 Nominal Inches
Nut Style:	Clinch
Nut Diameter:	0.312 Inches Nominal
Nut Height:	0.149 Inches Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this plain clinch nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3">https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3">https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3">https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3">https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3">https://military-fasteners.com/nuts/plain+clinch+nuts/CLS-632-3</a> and selecting the quantity you want the properties of the proper