

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2162-5-4](#)

SKU / Model:

CR2162504

Minimum Qty (MOQ):

100

NSN:

5320-00-054-8411

Schedule B:

7616.10.3000

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR2162-5-04 Specifications

| | |
|---|--|
| Fastener Length: | 0.388 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | H-38 Strain Hardened Locking Ring |
| Material: | Aluminum Alloy 5056 Locking Ring |
| Material Document And Classification: | Qq-a-430 Mil Spec Single Material Response Locking Ring |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2162-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.