

**Description**

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2162-5-4](#)

SKU / Model:

CR2162504

Minimum Qty (MOQ):

100

NSN:

5320-00-054-8411

Schedule B:

7616.10.3000

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N CR2162-5-04 Specifications

<b>Fastener Length:</b>	0.388 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Heat Treatment:</b>	H-38 Strain Hardened Locking Ring
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material Document And Classification:</b>	Qq-a-430 Mil Spec Single Material Response Locking Ring
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2162-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.