

Description

Fastener Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR216255
Minimum Qty (MOQ):	100
NSN:	5320-01-019-1528
Schedule B:	7616.10.3000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N CR2162-5-5 Specifications

Fastener Length:	0.438 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.286 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2017 Overall Or Aluminum Alloy 7075 Overall Or Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec 1st Material Response Overall Or Qq-a-430 Fed Spec 2nd Material Response Overall Or Qq-a-430 Fed Spec 3rd Material Response Overall
Surface Treatment:	Anodize Body
Surface Treatment:	Anodize Stem
Surface Treatment Document And Classification:	11815-no. 1200 Mfr Ref Single Treatment Response Stem
Surface Treatment Document And Classification:	11815-no. 205 Mfr Ref Single Treatment Response Body

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2162-5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.