

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR216257
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-019-9459
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N CR2162-5-7 Specifications

Fastener Length:	0.563 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Head Major Diameter:	0.286 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Stem
Material:	Aluminum Alloy 2017 Body Or Aluminum Alloy 7075 Body
Material Document And Classification:	Qq-a-430 Fed Spec All Material Responses Body
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Body
Surface Treatment:	Anodize Stem
Surface Treatment Document And Classification:	11815 Mfr Ref Single Treatment Response Stem
Surface Treatment Document And Classification:	11815 Mfr Ref Single Treatment Response Body

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2162-5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.