

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR216257
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-019-9459
Schedule B:	7616.10.3000
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N CR2162-5-7 Specifications

<b>Fastener Length:</b>	0.563 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Head Major Diameter:</b>	0.286 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Stem
<b>Material:</b>	Aluminum Alloy 2017 Body Or Aluminum Alloy 7075 Body
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec All Material Responses Body
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Body
<b>Surface Treatment:</b>	Anodize Stem
<b>Surface Treatment Document And Classification:</b>	11815 Mfr Ref Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	11815 Mfr Ref Single Treatment Response Body

## How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2162-5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.