



Military-Fasteners.com

P/N CR2162-6-6

## Description

Fastener Length: 1/2",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	CR216266
Minimum Qty (MOQ):	100
NSN:	5320-00-012-0747
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N CR2162-6-6 Specifications

<b>Fastener Length:</b>	0.537 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.352 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Heat Treatment:</b>	H-38 Strain Hardened Locking Ring
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Locking Ring
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1399 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2162-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.