

Description

diameter: 1/8", grip range: 0.025" - 0.062", wiredaw, universal head, aluminum stem, aluminum sleeve

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2163-4-1](#)

SKU / Model:	CR2163401
Minimum Qty (MOQ):	100
NSN:	5320-00-948-7347
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR2163-4-01 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.198 Inches Nominal
Head Style:	Oval Washer
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging Shank W/grooved End For Locking
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Heat Treatment:	T-4 Solution Heat Treated Sleeve
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2163-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.