

## Description

diameter: 1/8", grip range: 0.126" - 0.187", universal head, aluminum stem, aluminum sleeve, CR2163 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

## Additional Information

### Alternate Part Numbers

[NAS1398D4-3](#) [CR2163-4-3](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR2163403           |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-069-0055    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N CR2163-4-03 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Yellow   |
| <b>Fastener Length:</b>                               | 0.323 Inches Nominal   |
| <b>Head Style:</b>                                    | Oval Washer  |
| <b>Head Height:</b>                                   | 0.054 Inches Minimum And 0.064 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.125 Inches Nominal   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.238 Inches Minimum And 0.262 Inches Maximum  |
| <b>Expansion Device:</b>                              | Plain Stem-type T  |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum  |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Sleeve   |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Stem   |
| <b>Material:</b>                                      | Aluminum Alloy 2017 Sleeve   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem  |
| <b>Surface Treatment:</b>                             | Chromate Stem  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve And Chromate Sleeve   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2163-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.