

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR216342
Minimum Qty (MOQ):	100
NSN:	5320-00-993-7361
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2163-4-2 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.260 Inches Nominal
Head Style:	Oval Washer
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging Shank W/grooved End For Locking
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Heat Treatment:	H-38 Strain Hardened Locking Ring
Heat Treatment:	T-4 Solution Heat Treated Sleeve
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2163-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.