

Description

diameter: 5/32", grip range: 0.126" - 0.187", wiredaw, universal head, aluminum stem, aluminum sleeve

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2163-5-3](#)

SKU / Model:	CR2163503
Minimum Qty (MOQ):	100
NSN:	5320-00-889-2635
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N CR2163-5-03 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	0.313 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.063 Inches Nominal
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Heat Treatment:</b>	H-38 Strain Hardened Locking Ring
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Sleeve
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material:</b>	Aluminum Alloy 7075 Stem
<b>Material:</b>	Aluminum Alloy 2017 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Stem
<b>Surface Treatment:</b>	Anodize Sleeve Or Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2163-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.