

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2163-5-03](#)

SKU / Model:

CR216353

Minimum Qty (MOQ):

100

NSN:

5320-00-889-2635

Schedule B:

7616.10.3000

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets



P/N CR2163-5-3 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.313 Inches Nominal
Head Style:	Universal
Head Height:	0.063 Inches Nominal
Shank Diameter:	0.156 Inches Nominal
Head Major Diameter:	0.312 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Heat Treatment:	H-38 Strain Hardened Locking Ring
Heat Treatment:	T-4 Solution Heat Treated Sleeve
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2163-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.