

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR216385
Minimum Qty (MOQ):	25 EA
NSN:	5320-00-006-2576
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2163-8-5 Specifications

Fastener Length:	0.510 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.215 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	1970 Single Pounds Per Square Inch
Heat Treatment:	H-38 Strain Hardened Locking Ring
Material:	Aluminum Alloy 5056 Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1398 Professional/Industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2163-8-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.