

Description

diameter: 1/8", grip range: 0.126" - 0.187", bulbed, 100 degree flush head, aluminum sleeve, inconel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2238-4-3](#)

SKU / Model:	CR2238403
Minimum Qty (MOQ):	100
NSN:	5320-00-451-9162
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR2238-4-03 Specifications

<b>Fastener Length:</b>	0.344 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Shear Strength:</b>	619 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Surface Treatment:</b>	Anodize Body Or Oxide Film Body
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body
<b>Specification/standard Data:</b>	80205-nas1739 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.