

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR223841
Minimum Qty (MOQ):	100
NSN:	5320-01-019-1529
Schedule B:	7616.10.3000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CR2238-4-1 Specifications

Fastener Length:	0.220 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.140 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.225 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.045 Inches Minimum And 0.062 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Body Or Nickel Alloy Body
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Body Or Qq-w-390 Fed Spec 2nd Material Response Body Or Qq-n-281 Fed Spec 2nd Material Response Body
Surface Treatment:	Anodize Body Or Chromate Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-4-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.