

Description

Fastener Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR223841
Minimum Qty (MOQ):	100
NSN:	5320-01-019-1529
Schedule B:	7616.10.3000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N CR2238-4-1 Specifications

<b>Fastener Length:</b>	0.220 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.140 Inches Nominal
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.225 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.045 Inches Minimum And 0.062 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Body Or Nickel Alloy Body
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec 1st Material Response Body Or Qq-w-390 Fed Spec 2nd Material Response Body Or Qq-n-281 Fed Spec 2nd Material Response Body
<b>Surface Treatment:</b>	Anodize Body Or Chromate Body
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-4-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.