

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR223843
Minimum Qty (MOQ):	100
NSN:	5320-00-451-9162
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2238-4-3 Specifications

Fastener Length:	0.344 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Shear Strength:	619 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Body Or Oxide Film Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body
Specification/standard Data:	80205-nas1739 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.