

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | CR223857   |
| Minimum Qty (MOQ):      | 100  |
| NSN:                    | 5320-01-023-6232                                 |
| Schedule B:             | 7616.10.3000                                     |
| ECCN:                   | EAR99  |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR2238-5-7 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.625 Inches Maximum   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                         |
| <b>Shank Diameter:</b>                                | 0.172 Inches Minimum And 0.176 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.290 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.376 Inches Minimum And 0.437 Inches Maximum  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                                      | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring                                       |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Locking Ring  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve Or Chromate Sleeve  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| <b>Specification/standard Data:</b>                   | 80205-nas1739 Professional/Industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.