

Description

Fastener Length: 1-3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR223866
Minimum Qty (MOQ):	100
NSN:	5320-01-048-0571
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR2238-6-6 Specifications

<b>Fastener Length:</b>	1.437 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.063 Inches Nominal
<b>Shank Diameter:</b>	0.203 Inches Nominal
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.353 Inches Nominal
<b>Expansion Device:</b>	Drive Stem-type H
<b>Grip Length:</b>	0.375 Inches Nominal
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
<b>Material:</b>	Nickel Alloy 600 Stem
<b>Material Document And Classification:</b>	Ams 5665 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Specification/standard Data:</b>	80205-nas1739 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.