

Description

Fastener Length: 1-3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | CR223866 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-048-0571 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2238-6-6 Specifications

| | |
|--|--|
| Fastener Length: | 1.437 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Head Height: | 0.063 Inches Nominal |
| Shank Diameter: | 0.203 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.353 Inches Nominal |
| Expansion Device: | Drive Stem-type H |
| Grip Length: | 0.375 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring |
| Material: | Nickel Alloy 600 Stem |
| Material Document And Classification: | Ams 5665 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Specification/standard Data: | 80205-nas1739 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2238-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.