

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | CR223956 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-142-6301 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



NO IMAGE
AVAILABLE

P/N CR2239-5-6 Specifications

| | |
|---|--|
| Fastener Length: | 0.562 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Nickel Alloy 600 Stem |
| Material Document And Classification: | Ams5665 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Specification/standard Data: | 80205-nas1738 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2239-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.