

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | CR223964 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-115-8235 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N CR2239-6-4 Specifications

| | |
|---|--|
| Fastener Length: | 0.469 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.200 Inches Minimum And 0.204 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Nickel Alloy 600 Stem |
| Material Document And Classification: | Ams 5665 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Specification/standard Data: | 80205-nas1738 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2239-6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.