

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR223964            |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-01-115-8235    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



NO IMAGE  
AVAILABLE

## P/N CR2239-6-4 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.469 Inches Maximum   |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.080 Inches Minimum And 0.090 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.200 Inches Minimum And 0.204 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.356 Inches Minimum And 0.394 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.188 Inches Minimum And 0.250 Inches Maximum  |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>                                      | Nickel Alloy 600 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5665 Assn Std Single Material Response Stem  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve Or Chromate Sleeve  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| <b>Specification/standard Data:</b>                   | 80205-nas1738 Professional/industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2239-6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.