

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | CR224541 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-088-9223 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N CR2245-4-1 Specifications

| | |
|---|--|
| Fastener Length: | 0.320 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.087 Inches Minimum And 0.093 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.143 Inches Nominal |
| Expansion Device: | Break Stem |
| Grip Length: | 0.173 Inches Minimum And 0.193 Inches Maximum |
| Shear Strength: | 490 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 5056 Body |
| Material: | Nickel Alloy Locking Ring |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Ams 6322 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Body |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Locking Ring |
| Surface Treatment: | Anodize Body Or Chromate Body |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Body Or Mil-c-5541 Mil Spec Single Treatment Response Body |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2245-4-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.