

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR224542
Minimum Qty (MOQ):	100
NSN:	5320-01-088-9222
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR2245-4-2 Specifications

Fastener Length:	0.237 Inches Minimum And 0.257 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.140 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.143 Inches Nominal
Expansion Device:	Break Stem
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Body
Material:	Nickel Alloy Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Anodize Body And Chromate Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body And Mil-c-5541 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-a-416,type 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2245-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.