

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | CR224545 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-088-9219 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N CR2245-4-5 Specifications

| | |
|---|---|
| Fastener Length: | 0.429 Inches Minimum And 0.449 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.087 Inches Minimum And 0.093 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.143 Inches Nominal |
| Expansion Device: | Break Stem |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Material: | Aluminum Alloy 5056 Body |
| Material: | Nickel Alloy Locking Ring |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Ams 6322 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Body |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Locking Ring |
| Surface Treatment: | Anodize Body And Chromate Body |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Body And Mil-c-5541 Mil Spec 2nd Treatment Response Body |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2245-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.