

Description

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR224552
Minimum Qty (MOQ):	100
NSN:	5320-01-089-1391
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR2245-5-2 Specifications

<b>Fastener Length:</b>	0.410 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Head Major Diameter:</b>	0.176 Inches Nominal
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.259 Inches Minimum And 0.279 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Body
<b>Material:</b>	Nickel Alloy Locking Ring
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-w-390 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Body
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Body Or Mil-c-5541 Mil Spec Single Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2245-5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.