

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR224553
Minimum Qty (MOQ):	100
NSN:	5320-01-089-1392
Schedule B:	8803.30.0030
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR2245-5-3 Specifications

Fastener Length:	0.323 Inches Minimum And 0.343 Inches Maximum
Head Style:	Flat Washer
Head Height:	0.047 Inches Nominal
Shank Diameter:	0.109 Inches Minimum And 0.115 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.208 Inches Minimum And 0.218 Inches Maximum
Expansion Device:	Break Stem
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Aluminum Alloy 5056 Body
Material:	Nickel Alloy Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 F Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Anodize Body And Chromate Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body And Mil-c-5541 Mil Spec 2nd Treatment Response Body
Surface Treatment Document And Classification:	Qq-a-416 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2245-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.