

**Description**

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR224553
Minimum Qty (MOQ):	100
NSN:	5320-01-089-1392
Schedule B:	8803.30.0030
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR2245-5-3 Specifications

<b>Fastener Length:</b>	0.323 Inches Minimum And 0.343 Inches Maximum
<b>Head Style:</b>	Flat Washer
<b>Head Height:</b>	0.047 Inches Nominal
<b>Shank Diameter:</b>	0.109 Inches Minimum And 0.115 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.208 Inches Minimum And 0.218 Inches Maximum
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Body
<b>Material:</b>	Nickel Alloy Locking Ring
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 F Fed Spec Single Material Response Body
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Locking Ring
<b>Surface Treatment:</b>	Anodize Body And Chromate Body
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Body And Mil-c-5541 Mil Spec 2nd Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Qq-a-416 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2245-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.