

Description

Fastener Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR2248509
Minimum Qty (MOQ):	100
NSN:	5320-00-410-0012
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



NO IMAGE
AVAILABLE

P/N CR2248-5-09 Specifications

Fastener Length:	0.750 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-5-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.