

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2248-5-02](#)

SKU / Model:	CR224852
Minimum Qty (MOQ):	100
NSN:	5320-00-800-6274
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2248-5-2 Specifications

Fastener Length:	0.312 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Overall
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material Document And Classification:	Qq-a-430, 5056f Fed Spec Single Material Response Overall
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Fed Spec All Treatment Responses Stem
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.