

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2248-5-06](#)

SKU / Model:	CR224856
Minimum Qty (MOQ):	100
NSN:	5320-00-143-6395
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR2248-5-6 Specifications

<b>Fastener Length:</b>	0.562 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Surface Treatment:</b>	Anodize Sleeve Or Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1739 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.