

Description

diameter: 3/16", grip range: 0.126" - 0.187", bulbed, flush head, aluminum sleeve, steel stem, CR2248 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2248-6-3](#)

SKU / Model:	CR2248603
Minimum Qty (MOQ):	100
NSN:	5320-00-916-9534
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR2248-6-03 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Minimum And 0.188 Inches Maximum
Shear Strength:	619 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment Document And Classification:	Mil-c-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.