

**Description**

diameter: 3/16", grip range: 0.188" - 0.250", bulbed, 100 degree flush head, 5056 aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR2248-6-4](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR2248604           |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-728-8567    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR2248-6-04 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.418 Inches Nominal   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                         |
| <b>Shank Diameter:</b>                                | 0.188 Inches Nominal   |
| <b>Head Major Diameter:</b>                           | 0.349 Inches Minimum And 0.357 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.188 Inches Minimum And 0.250 Inches Maximum  |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>                                      | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring                                       |
| <b>Material:</b>                                      | Steel Comp 8740 Stem   |
| <b>Material Document And Classification:</b>          | Ams6322 Assn Std Single Material Response Stem   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve  |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Locking Ring  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve Or Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Stem And Chromate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty2 Fed Spec Single Treatment Response Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.