

Description

diameter: 3/16", grip range: 0.313" - 0.375", bulbed, 100 degree flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR2248-6-6](#)

SKU / Model:	CR2248606
Minimum Qty (MOQ):	100
NSN:	5320-00-152-5911
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR2248-6-06 Specifications

Fastener Length:	0.594 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Shear Strength:	1260 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp E4340 Stem Or Steel Comp 8740 Stem
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-6-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.