

Description

Fastener Length: 7/8", CR2248 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | CR2248612 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-166-5345 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N CR2248-6-12 Specifications

| | |
|---|--|
| Fastener Length: | 0.923 Inches Minimum And 0.943 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.200 Inches Minimum And 0.204 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.349 Inches Minimum And 0.357 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.688 Inches Minimum And 0.750 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Nickel Alloy Locking Ring |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Ams6322 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Locking Ring |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.