



Military-Fasteners.com

P/N CR2248-6-7

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR224867
Minimum Qty (MOQ):	100
NSN:	5320-00-369-5126
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR2248-6-7 Specifications

Fastener Length:	0.603 Inches Minimum And 0.623 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp E4340 Stem Or Steel Comp 4340 Stem Or Steel Comp 8740 Stem
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Stem Or Mil-s-5000 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem
Material Document And Classification:	Q-a-430 Fed Spec 13th Material Response Sleeve
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2248-6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.