

Description

diameter: 1/8", grip range: 0.063" - 0.125", bulbed, universal head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2249-4-2](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | CR2249402 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-800-6275 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N CR2249-4-02 Specifications

| | |
|---|--|
| Fastener Length: | 0.237 Inches Minimum And 0.257 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.139 Inches Minimum And 0.143 Inches Maximum |
| Head Major Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Special Features: | Lock Ring Nickel-copper Alloy Qq-n-281 |
| Material: | Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment: | Cadmium Stem And Chromate Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1738 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.