

Description

diameter: 1/8", grip range: 0.313" - 0.375", bulbed, universal head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2249-4-6](#)

SKU / Model:

CR2249406

Minimum Qty (MOQ):

100

NSN:

5320-00-189-8695

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR2249-4-06 Specifications

Fastener Length:	0.488 Inches Minimum And 0.508 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Material:	Aluminum Alloy 5056 Body
Material:	Nickel Alloy Sleeve
Material:	Steel Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Oxide Film Body Or Anodize Body
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Body Or Mil-a-8625 Mil Spec 2nd Treatment Response Body
Specification/standard Data:	80205-nas1738 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.