

Description

Fastener Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2249-4-05](#)

SKU / Model:	CR224945
Minimum Qty (MOQ):	100
NSN:	5320-00-369-5132
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR2249-4-5 Specifications

Fastener Length:	0.424 Inches Minimum And 0.444 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.