

Description

diameter: 5/32", grip range: 0.063" - 0.125", bulbed, universal head, 5056 aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR2249-5-2](#)

| | |
|-------------------------|---|
| SKU / Model: | CR2249502 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-779-0292 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2249-5-02 Specifications

| | |
|---|--|
| Fastener Length: | 0.259 Inches Minimum And 0.279 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Shear Strength: | 976 Single Pounds Per Square Inch |
| Special Features: | Lock Ring Nickel-copper Alloy Qq-n-281 |
| Material: | Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment: | Cadmium Stem And Chromate Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.