

**Description**

diameter: 5/32", grip range: 0.188" - 0.250", bulbed, universal head, 5056 aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR2249504
Minimum Qty (MOQ):	100
NSN:	5320-00-949-3929
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N CR2249-5-04 Specifications

<b>Fastener Length:</b>	0.387 Inches Minimum And 0.407 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	935 Single Pounds Per Square Inch
<b>Special Features:</b>	Lock Ring Nickel-copper Alloy Qq-n-281
<b>Material:</b>	Aluminum Alloy 5056 Bolt
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy X-750 Sleeve
<b>Material:</b>	Steel Comp 4340 Nut Or Steel Comp 8740 Nut
<b>Material Document And Classification:</b>	Ams 6415 Assn Std 1st Material Response Nut Or Ams 6322 Assn Std 2nd Material Response Nut
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Bolt
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Anodize Bolt
<b>Surface Treatment:</b>	Anodize Nut Or Cadmium Nut Or Chromate Nut
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-8625,ty 2,cl @1 Mil Spec 1st Treatment Response Nut Or Mil-a-8625,ty 2,cl 2 Mil Spec 2nd Treatment Response Nut
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Bolt
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1738 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.