

Description

Fastener Length: 13/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | CR224951 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-964-0720 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CR2249-5-1 Specifications

| | |
|---|--|
| Fastener Length: | 0.195 Inches Minimum And 0.215 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.025 Inches Minimum And 0.062 Inches Maximum |
| Shear Strength: | 976 Single Pounds Per Square Inch |
| Material: | Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Surface Treatment: | Anodize Stem And Chromate Stem |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1738 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-5-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.