

Description

Fastener Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR2249510
Minimum Qty (MOQ):	100
NSN:	5320-00-189-8715
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2249-5-10 Specifications

Fastener Length:	0.812 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-n-271 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Anodize Sleeve Or Oxide Film Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1738 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.