

P/N CR2249-5-4

Description

Fastener Length: 3/8", CR2249 series rivet

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR2249-5-04

SKU / Model: CR224954

Minimum Qty (MOQ): 100

NSN: 5320-00-949-3929

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N CR2249-5-4 Specifications

| Fastener Length: | 0.387 Inches Minimum And 0.407 Inches Maximum |
|--|---|
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 935 Single Pounds Per Square Inch |
| Special Features: | Lock Ring Nickel-copper Alloy Qq-n-281 |
| Material: | Aluminum Alloy 5056 Bolt |
| Material: | Nickel Alloy 400 Sleeve Or Nickel Alloy X-750 Sleeve |
| Material: | Steel Comp 4340 Nut Or Steel Comp 8740 Nut |
| Material Document And Classification: | Ams 6415 Assn Std 1st Material Response Nut Or Ams 6322 Assn Std 2nd Material Response Nut |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Bolt |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Anodize Bolt |
| Surface Treatment: | Anodize Nut Or Cadmium Nut Or Chromate Nut |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-8625,ty 2,cl @1 Mil Spec 1st Treatment Response Nut Or Mil-a-8625,ty 2,cl 2 Mil Spec 2nd Treatment Response Nut |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Bolt |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve |
| Specification/standard Data: | 80205-nas1738 Professional/industrial Association Standard |
| | |

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR2249-5-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR2249-5-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR2249-5-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR2249-5-4 and selecting the quantity you want then