

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2249-5-05](#)

SKU / Model:	CR224955
Minimum Qty (MOQ):	100
NSN:	5320-00-937-5448
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2249-5-5 Specifications

Fastener Length:	0.461 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	596 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Mil-s-5541 Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1738 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.