

Description

diameter: 3/16", grip range: 0.188" - 0.250", bulbed, universal head, 5056 aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR2249-6-4](#)

SKU / Model:

CR2249604

Minimum Qty (MOQ):

100

NSN:

5320-00-779-0301

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets



P/N CR2249-6-04 Specifications

| | |
|---|--|
| Fastener Length: | 0.415 Inches Minimum And 0.435 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.201 Inches Minimum And 0.205 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 1390 Single Pounds Per Square Inch |
| Special Features: | Lock Ring Nickel-copper Alloy Qq-n-281 |
| Material: | Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Surface Treatment: | Anodize Sleeve And Chromate Sleeve |
| Surface Treatment: | Cadmium Stem And Chromate Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1738 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.